



Electrical Test :

- 100% Test(Open, Short, Miss Wire)
- Contact Resistance: 5 ohm Max.
- Insulation Resistance: 10M ohm Min.

Specification :

- | | |
|-----------------|---|
| 1 Cable | UL2725, 28AWG(BC)*1P+26AWG(BC)*2C+AE+B(80/0.10TCCS),
OD: 3.7±0.2 mm, Jacket: Transparent PVC |
| 2 Conn.1 | USB Type C Plug, Shell: Nickel Plated, Insulator: Black |
| 3 Conn.2 | D-Sub 9 Plug, with PCB, Shell: Nickel Plated |
| 4 Outer Molding | PVC: 45P, Color: Transparent Black |

Rev.	Date	Contents of Change	Designer	Tol±	Pl	Met	Ins	Por	Cab	Pac	Gas	Dis	Approve	Check	Draw	Design	Product Name	ROLINE Converter Cable USB C-RS232, DB9, 1.8m, Transparent Black				
△				Range									Allen	Allen	Philip	2017-08-31	Product No.	12.02.1161	R00			
△				0~6	0.1	0.1	0.1	0.2	0.5	1	0.5	0.2										
△				6~30	0.1	0.1	.15	.25	1	1	0.5	.25										
△				30~80	0.1	.15	0.2	0.3	2	1.5	1	0.3										
△				80~180	.15	.15	.25	0.3	2	2	1	.45										
△				180~315	.15	0.2	0.3	0.4	2.5	2	1	0.6										
△				315~800	0.2	0.3	0.4	0.5	3	3	2	1.1										



Scale 1:1 Unit mm