



PIN OUT




NOTE:

1. Fluke Channel Test ISO 11801 channel Class Ea
2. RoHS2.0 AND REACH compliant
3. Electrical test: 100% open short & miss wire test;
4. OPERATING TEMPERATURE: -10°C ~ 60°C
5. Print word: CAT6A U/UTP 4x2x32AWG/7 LSZH ISO11801 & EN50173 & ANSI/TIA568C.2

MATERIAL LIST

③	CABLE	CAT. 6A U/UTP CABLE (32AWG BC*1P)*4+JACKET:LSZH/WHITE, OD:3.4±0.2mm	1	
②	Over mold	48P PVC/WHITE	2	
①	Plug	RJ45 8P8C Unshielded Plug, PIN GOLD PLATED 3u", TRANSPARENT	2	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

ITEM No.	LENGTH
21.15.0980	500±30mm
21.15.0981	1000±30mm
21.15.0984	1500±50mm
21.15.0982	2000±50mm
21.15.0983	3000±70mm
21.15.0985	5000±70mm



DESC. ROLINE Cat. 6A UTP Patch Cord, LSZH, Slim, White

