

# ROLINE PCI-Express x4 Adapter, 2x Ports Type C USB 3.2 Gen 2

<b>Product No.</b>	15.06.2143
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	15.06.2143
<b>EAN (single piece)</b>	7611990130962



Expand your PC with two SuperSpeed+ USB 3.1 ports.

- USB3.1 PCIe x4 Lane Host Adapter
- USB 3.1 offers Super Speed+ data transfer rates of up to 10 Gbit/s
- Connectors: 2x USB 3.1 Type C downstream connectors on board
- Compliant with Universal Serial Bus 3.1 Specification Revision 1.0
- Compliant with Intel eXtensible Host Controller Interface (xHCI) Specification 1.0
- Compliant with USB Attached SCSI Protocol Specification 1.0
- Compliant with PCI Express Specification 3.0
- Supports 5V3A USB bus power each USB 3.1 Type C port
- Supports PCIe 1.0 and PCIe 2.0 and PCIe 3.0 motherboard
- Support USB3.1, USB3.0, USB2.0 and USB1.1 devices
- Low Profile PCIe Form Factor
- Low profile PCI form factor (additional low profile PCI bracket included)
- Built-in 15-pin SATA power connector for the power supply of the USB ports
- Require an empty PCIe 2.0 or PCIe 3.0 x4 or x8 or x16 slot in computer for USB3.1 full

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

## Technical specifications

Manufacturer	ROLINE
--------------	--------

Product group	I/O Card
Product type	PCI-Express Adapter
Colour	red
Scope of delivery	Adapter, low profile bracket, driver CD, manual
BUS system	PCI Express
Interface	USB 3.1
USB 2.0 Interface	Yes
USB 3.0 Interface	Yes
USB 3.1 Interface	Yes
Data transfer rate	10 Gbit/s
Operating System	Windows 10 / 8.1/ 8 / 7 / Vista / 2012
Connection ports	2x USB 3.1 Type C, external
Mounting height	Full profile
Installation Guide/Manual	Yes
Weight	43.2 g
Height of packaging (single piece)	50 mm
Width of packaging (single piece)	160 mm
Depth of packaging (single piece)	220 mm
Package weight (single piece)	0.16 kg