

mSATA SSD – SATA

Convert Fast Speed mSATA SSD to SATA host port connection!

This manual supports following Product Models:

- **Model with 1.8” frame:** Convert 3.3V mSATA SSD to 3.3V 1.8” SATA Form Factor
- **Model with 2.5” frame:** Convert mSATA SSD to 2.5” SATA Form Factor that Includes 2.5 “drive metal frame with 8 mounting holes
- **Model with 3.5” frame:** Convert mSATA SSD to 3.5” SATA Form Factor that Includes 3.5 “drive metal frame with mounting holes
- **Model with PCI bracket:** Convert mSATA SSD to PCI Form Factor that Includes Regular size and Low Profile two PCI Brackets
- **Model of DOM:** 7pin SATA latch connector and 4Pin power wafer connector on board

1. Features

- mSATA SSD can be the primary bootable device containing the OS and application.
- Transparent to the operating system and does not require any driver
- Supports SATA I, SATA II and SATA III (6Gbps)
- Supports Windows, Mac and Linux OS
- Fully RoHS compliant

2. Installation

Step 1. Plug mSATA SSD card into 52-pin mSATA socket on board, push the other end of mSATA SSD card down and screw (or latch) to PCB.

Step 2. Connect SATA Signals & Power connectors.