



**WIRE ADDRESS**

- |    |    |     |    |    |     |           |
|----|----|-----|----|----|-----|-----------|
| P1 | 1  | —○— | P2 | 1  | —○— | CENTER    |
|    | 6  | —○— |    | 6  | —○— | GND       |
|    | 2  | —○— |    | 2  | —○— | CENTER    |
|    | 7  | —○— |    | 7  | —○— | GND       |
|    | 3  | —○— |    | 3  | —○— | CENTER    |
|    | 8  | —○— |    | 8  | —○— | GND       |
|    | 4  | —○— |    | 4  | —○— | Blue Coax |
|    | 5  | —○— |    | 5  | —○— |           |
|    | 9  | —○— |    | 9  | —○— |           |
|    | 10 | —○— |    | 10 | —○— |           |
|    | 11 | —○— |    | 11 | —○— |           |
|    | 12 | —○— |    | 12 | —○— |           |
|    | 13 | —○— |    | 13 | —○— |           |
|    | 14 | —○— |    | 14 | —○— |           |
|    | 15 | —○— |    | 15 | —○— |           |
|    | 64 | —○— |    | 64 | —○— |           |

- Electrical Test:
- 1.100% TEST OPEN SHORT MIS-WIRE.
  - 2.CONTACT RESISTANCE:3Ω MAX.
  - 3.INSULATION RESISTANCE:5MΩ MIN.
  - 4.HI-POT:300V DC/10MS.
  - 5.Real Test Passed 1280\*1024.
  - 6.Real Test Not Twinkling, Double Vision and Decolor.

E	45P BLACK PVC	G
D	Ferrite Core (17.5*28.5*9.5mm)	PCS
C	HD37.7 Screw	PCS
B	HDB15P MALE (Black Insulator- Nickel Plated)	PCS
A	UL2919,28# 3COAX+28#*9C+ADB, OD=8.0mm BLACK DENTATE PVC JACKET.	PCS
NUMBER	PRODUCT SPECIFICATIONS	Quantity Unit
1	2	4

ROLINE High Quality Cable with Ferrite + DDC, HD15 M - HD15 M, 3.0m	
Item	11.04.5653
Draw	<i>Make</i> Date: 2020.08.18
Approval	
Duty	F16 BOM.NO.:13927
Sample NO.	Drawings of 1 (2) Proportion: 1:1 Unit(mm)  A4

