

STANDARD DisplayPort Cable, DP-DP, M/M, black, 2 m

| | | |
|-------------------------|------------|----------------|
| Product No. | 11.55.3686 | SECOMP® |
| Manufacturer | SECOMP | |
| Manufacturer No. | 11.55.3686 | |



STANDARD DisplayPort Cable with DP connection on both sides for connecting an Ultrabook, Notebook/Laptop or PC to a monitor, TV or projector - for screen transmissions in excellent quality with resolutions of up to 3840x2160 / 4096x2560 @60Hz!

- DisplayPort is a universal connection standard for the transmission of picture and sound signals. Applications include mainly the connection of monitors and televisions to computers, BluRay players and similar devices.
- The connector requires less space and is therefore more suitable for portable display devices (ultrabooks, notebooks/laptops) or for 2 connectors on a graphics card (on a slot plate).
- The practical plug design prevents the cable from slipping out of the DisplayPort socket.
- Compliant DP v1.2 (max. 4096 x 2560 @60Hz)

Technical specifications

| | |
|---------------|--------------------|
| Manufacturer | SECOMP |
| Product group | Cable |
| Product type | DisplayPort Cables |
| Colour | black |
| Length | 2 m |

| | |
|------------------------------------|------------------------|
| Scope of delivery | DisplayPort Cable |
| Transfer quality | DisplayPort v1.2 |
| Max. resolution | 4096 x 2560 @60Hz (4K) |
| side 1 connector | DisplayPort M |
| side 2 connector | DisplayPort M |
| Side 1 Connector Type | DisplayPort |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | DisplayPort |
| Side 2 Connector Gender | Male |
| Colour (Cable) | black |
| Area of application | External |
| Cable shielding | Screened |
| Weight | 85 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 100 mm |
| Package weight (single piece) | 0.12 kg |