

# ROLINE RS-232 to RS-422/485 Converter, Din Rail, self powered

Product No.	12.02.1008
Manufacturer	ROLINE
Manufacturer No.	12.02.1008
EAN (single piece)	7611990198665



Converts RS-422 or RS-485 devices to a RS-232 port

- Connectors: RS-232: DB9 Female, RS-422/485: 7-pin terminal block
- High speed baud rate up to 921.6 Kbit/s
- Data transfer rate of up to 115.2 Kbit/s at 1.2 km
- Built-in Terminator 120 Ohm by DIP switch settings
- Signals for RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
- Signals for RS-422/4-wire: Tx+, Tx-, Rx+, Rx-, GND
- Signals for RS-485/2-wire: D+, D-, GND
- Windows ME/2000/Server 2003/XP/Server 2008/XP/Vista/7/10/11
- Protection: 15 KV ESD protection for all signals, 600 W surge protection for RS-422/485 signals
- For DIN rail mounting (DIN rail kit included) or desktop use
- Hardware solution, no software required
- RS-232 port powered technology, optional: Power input 10~30 VDC
- Contents: Converter, manual

Technical specifications	
Manufacturer	ROLINE
Product group	Adapters, Terminators, Converters
Product type	Serial interface converter
Colour	black

Scope of delivery	Converter, manual
Dimensions (HxWxD)	22 x 42 x 97,2 mm
Height	22 mm
Width	42 mm
Depth	97.2 mm
Weight	62.9 g
Height of packaging (single piece)	40 mm
Width of packaging (single piece)	140 mm
Depth of packaging (single piece)	200 mm
Package weight (single piece)	0.14 kg