ROLINE DisplayPort Cable (AOC), v2.1, 10K@60Hz, 54Gbit/s, UHBR13.5, DP-DP, M/M, 20 m

Product No. 14.01.3502

Designed for Professional

Manufacturer ROLINE

Manufacturer No. 14.01.3502

EAN (single piece) 7630049634718





ROLINE DisplayPort AOC Cable with DP connection on both sides for connecting an Ultrabook, Notebook/Laptop or PC to a monitor, TV or projector - for screen transmissions in excellent quality with resolutions of up to 10240x4320 @60Hz!

• Total length of the end device distance (e. g. from notebook/laptop to beamer or PC to monitor): 20 meters

Hardware solution, no software required

- No external power supply required; the cable contains a copper fibre for power supply
- Small connector and cable dimensions; the cable has a smaller diameter than comparable cables made of pure copper due to the glass fibres.
- The practical plug design prevents the cable from slipping out of the DisplayPort socket.
- Outer diameter: 4.8±0.2mm
- Compliant DP v2.1 (max. 10240 x 4320 @60Hz)

| Technical specifications | | |
|--------------------------|-----------------------|--|
| Manufacturer | ROLINE | |
| Product group | Audio / video cable | |
| Product type | DisplayPort extension | |
| Colour | black | |
| Length | 20 m | |

| Scope of delivery | AOC Cable |
|------------------------------------|--------------------------|
| Transfer quality | DisplayPort v2.1 |
| Max. resolution | 10240 x 4320 @60Hz (10K) |
| Side 1 Connector Type | DisplayPort |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | DisplayPort |
| Side 2 Connector Gender | Male |
| Colour (Cable) | black |
| Area of application | External |
| Material (external cable mantle) | PVC |
| Operating temperature min. | 0 °C |
| Operating temperature max. | 50 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 70 °C |
| Height of packaging (single piece) | 0 mm |
| Width of packaging (single piece) | 0 mm |
| Depth of packaging (single piece) | 0 mm |
| Package weight (single piece) | 0 kg |