ROLINE EV Charging Cable Assembly Type2, 3-Phase, 480VAC (3P+N+E), 32 A, 22 kW, 7.5 m

roline

Product No. Manufacturer Manufacturer No. EAN (single piece)






19.08.0027

19.08.0027

ROLINE



Type2 charging cable for electric and hybrid cars with 22 kW, 3-phase, 480 V AC

- Enables easy / fast charging at public charging stations and private wall boxes (wallbox)
- Suitable for charging electric and hybrid vehicles
- Mode 3 / Type 2 car charging cable
- Connections: Type 2 on both sides
- For all electric cars with type 2 connection
- Ergonomically shaped plug and coupler

• Moisture protection (IP65 - connected state, IP54 - unconnected cable with protective caps attached)

- 32 A / 3- phase (480 VAC)
- Max. Charging power: 22 kW

Technical specifications	
Manufacturer	ROLINE
Product group	Power Cables
Product type	Electric car charging cable
Colour	black
Length	7.5 m
Scope of delivery	E-car charging cable, carrying bag

Charging power	22 kW
Current	32 A
Number of phases	3-phase
Supported charging technology	Mode-3
Side 1 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 1 Connector Gender	Male
Side 2 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 2 Connector Gender	Female
Cable LSOH	flame retardant
Protection class (IP Code)	IP65 IP54
Mains connection	IEC 62196-2 Type 2 plug, 3Ph.
Operating temperature min.	-30 °C
Operating temperature max.	50 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Height	40 mm
Width	390 mm
Depth	390 mm
Weight	2.6 kg
Height of packaging (single piece)	100 mm
Width of packaging (single piece)	370 mm
Depth of packaging (single piece)	370 mm

Package weight (single 5 kg piece)