ROLINE EV Charging Cable Assembly Type2, 1-Phase, 250VAC (1P+N+E), 32 A, 7.4 kW, spiral, 5 m

Product No. 19.08.0035

ROLINE

Manufacturer No. 19.08.0035

EAN (single piece) 7630049628168





Manufacturer





Type2 charging cable for electric and hybrid cars with 7.4 kW, 1-phase, 250 V AC

- Enables easy / fast charging at public charging stations and private wall boxes (wallbox)
- Suitable for charging electric and hybrid vehicles
- Mode 3 / Type 2 car charging cable
- Connections: Type 2 on both sides
- For all electric cars with type 2 connection
- Ergonomically shaped plug and coupler
- Moisture protection (IP65 connected state, IP54 unconnected cable with protective caps attached)
- Spiral, max. usable length 3 m
- 32A / 1- phase (250 VAC)
- Max. Charging power: 7,4 kW

Technical specifications		
Manufacturer	ROLINE	
Product group	Power Cables	
Product type	Electric car charging cable	
Colour	black	
Length	5 m	

Scope of delivery	E-car charging cable, carrying bag
Charging power	7.4 kW
Current	32 A
Number of phases	1-phase
Supported charging technology	Mode-3
Side 1 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 1 Connector Gender	Male
Side 2 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 2 Connector Gender	Female
Cable LSOH	flame retardant
Protection class (IP Code)	IP65 IP54
Technical particularity	spiral, max. usable length 3 m
Mains connection	IEC 62196-2 Type 2 plug, 1Ph.
Operating temperature min.	-30 °C
Operating temperature max.	50 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Height	80 mm
Width	360 mm
Depth	360 mm
Weight	2.1 kg
Height of packaging (single piece)	100 mm

Width of packaging (single piece)	370 mm
Depth of packaging (single piece)	370 mm
Package weight (single piece)	3 kg