## ROLINE Portable EV Charging Cable, Italian Plug - Type 2, Mode 2, 10 A, 2.3 kW, 7.5 m

**Product No.** 19.08.0127

Designed for Professi

Manufacturer

ROLINE

Manufacturer No.

19.08.0127

**EAN** (single piece)

7630049633612











## ROLINE Portable Charging Cable Mode 2 with Italian Plug (Type L) and Type 2 Connector for Electric and Hybrid Cars - with up to 2.3 kW.

- Enables easy and fast charging at home or on the go
- Suitable for charging electric and hybrid vehicles
- Connections: Type L /(Italian Plug) and Type 2 Connector
- For all electric or hybrid cars with Type 2 connection
- · Ergonomically shaped plug and coupler
- IP-Protection of Type 2 Connector: IP65 (mated) / IP54 (unmated)
- IP-Protection of IC-CPD (In-cable control and protection device): IP67
- 10 A / 1-phase (250 VAC)
- Max. Charging Power: 2,3 kW
- Flame retardant (IEC 60332-1)
- Halogen free (IEC 60754-1/2)

Technical specifications		
Manufacturer	ROLINE	
Product group	Power Cables	

Product type	Electric car charging cable
Colour	black
Length	7.5 m
Scope of delivery	Charging Cable, Carrying Bag, User Manual
Charging power	2.3 kW
Current	10 A
Number of phases	1-phase
Supported charging technology	Mode-2
Side 1 Connector Type	CEI23-50, Type-L
Side 1 Connector Gender	Male
Side 2 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 2 Connector Gender	Female
Material (external cable mantle)	TPU
Cable LSOH	flame retardant
Protection class (IP Code)	IP67 IP65 IP54
Technical particularity	Rated Current: 6/8/10A
Regional use	Italy, San Marino, Vatican City, Albania
Operating temperature min.	-30 °C
Operating temperature max.	50 °C
Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Height	80 mm

Width	360 mm
Depth	360 mm
Weight	2.875 kg
Height of packaging (single piece)	100 mm
Width of packaging (single piece)	340 mm
Depth of packaging (single piece)	340 mm
Package weight (single piece)	2.5 kg