

ROLINE LineSecure II 2000

Product No.	19.40.1120
Manufacturer	ROLINE
Manufacturer No.	19.40.1120
EAN (single piece)	7611990979769



LineSecure UPS's work with the "buck & boost" line interactive technology; used when reliable protection against strong voltage fluctuations is essential. Protect against: power failure, power sag, power surge, under voltage, over voltage.

Product features:

- Compact, quiet, user friendly
 - Desktop and 19" RM models
 - Short circuit and overload protection
 - AVR (Automatic Voltage Regulation)
 - ABM (Automatic Battery Management) increases battery life up to 50%
 - Telephone/Modem connections
 - Shutdown software including License for 1 server
 - Serial Port for advanced Power Management Software (incl, in content of delivery)
 - UPS Management Software : Windows NT/ 2k / XP / 7 / 8 /Server 2003 / 2008 / 2012 x86/x64,
MAC OS X (Intel) 10.6.x, 10.7.x, 10.8.x Mountain Lion, 10.9.x MavericksMAC OS, LINUX
- Content: UPS, Cable set, Software CD

Technical specifications

Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive

Colour	black
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive
Power class	2000 ... 3000 VA
Output (VA/W)	2000 / 1300
Efficiency	95 %
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	226 x 170 x 450 mm
Mounting form	Tower
Voltage (input)	230V +- 15%
Voltage (output)	230V
Frequency	50Hz
Connector type (input)	cold connector IEC320 C14
Outputs	6
Connector type (output)	6x cold connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	USB, RS232
RS-232 Interface	Yes
USB 2.0 Interface	Yes
Hot swap batteries	No
Bypass	No

Additional over current protector	Telephone/Fax
Activity	Display
Activity Display	LCD
incl.Management Software	Windows
Internal cooling	Active, fan
Ambient temperature	0-40°C
Operating temperature min.	0 °C
Operating temperature max.	40 °C
Height	226 mm
Width	170 mm
Depth	450 mm
Weight	30 kg
Height of packaging (single piece)	350 mm
Width of packaging (single piece)	300 mm
Depth of packaging (single piece)	550 mm
Package weight (single piece)	27.204 kg