
ROLINE Gigabit Ethernet Industrial Switch, 8x RJ45


Product No. 21.13.1163


Manufacturer ROLINE

Manufacturer No. 21.13.1163

EAN (single piece) 7630049635005







Gigabit Ethernet Network Switch with 8 ports for use in an industrial environment.

- Gigabit Ethernet switch with 8x 10/100/1000Base-T ports
- Supports auto-negotiation, auto-MDI/MDI-X
- For use in industrial environments
- Supports jumbo frames
- DIN rail mounting or via mounting plate
- Operating voltage: +8.0 to +57VDC
- Power consumption: 10W max.
- DC input via terminal block
- We recommend the DIN rail PSU 21.13.1311 / NDR-75-24

| Manufacturer ROLINE Product group Network Switches Product type Gigabit Ethernet Switch Colour black Scope of delivery Gigabit Ethernet Industrial Switch, Installation CD Network standard Gigabit Ethernet LAN (Mbps) 10/100/1000 Quantity of ports 8 | Technical specifications | |
|--|--------------------------|---|
| Product type Gigabit Ethernet Switch Colour black Scope of delivery Gigabit Ethernet Industrial Switch, Installation CD Network standard Gigabit Ethernet LAN (Mbps) 10/100/1000 | Manufacturer | ROLINE |
| Colour black Scope of delivery Gigabit Ethernet Industrial Switch, Installation CD Network standard Gigabit Ethernet LAN (Mbps) 10/100/1000 | Product group | Network Switches |
| Scope of delivery Gigabit Ethernet Industrial Switch, Installation CD Network standard Gigabit Ethernet LAN (Mbps) 10/100/1000 | Product type | Gigabit Ethernet Switch |
| Network standard Gigabit Ethernet LAN (Mbps) 10/100/1000 | Colour | black |
| LAN (Mbps) 10/100/1000 | Scope of delivery | Gigabit Ethernet Industrial Switch, Installation CD |
| | Network standard | Gigabit Ethernet |
| Quantity of ports 8 | LAN (Mbps) | 10/100/1000 |
| | Quantity of ports | 8 |

| Gigabit Ethernet Ports RJ-45 | 8 |
|---------------------------------------|-------------------------------|
| Mounting form | DIN Rail |
| Dimensions (HxWxD) | 42 x 106 x 140 mm |
| Power supply unit (internal/external) | External |
| Mains connection | Loose cable / screw terminals |
| Operating temperature min. | -30 °C |
| Operating temperature max. | 70 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 85 °C |
| Height | 42 mm |
| Width | 106 mm |
| Depth | 140 mm |
| Weight | 548 g |
| Height of packaging (single piece) | 70 mm |
| Width of packaging (single piece) | 160 mm |
| Depth of packaging (single piece) | 210 mm |
| Package weight (single | 0.65 kg |

piece)