

# ROLINE UTP Cable Cat.6 Component Level, LSOH, white, 3 m

**Product No.** 21.15.2563  
**Manufacturer** ROLINE  
**Manufacturer No.** 21.15.2563  
**EAN (single piece)** 7611990172160



Cat.6  
Class E

U/UTP

LSOH

COMPONENT  
Level Tested

Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Halogen-free, flame retardant, low smoke.

## 100 % Component level testing

| Technical specifications |                    |
|--------------------------|--------------------|
| Manufacturer             | ROLINE             |
| Product group            | Twisted Pair Cable |
| Product type             | UTP Patch Cables   |
| Colour                   | white              |
| Length                   | 3 m                |
| Shield type              | UTP                |
| Transfer quality         | Cat6 / Class E     |

|                                    |            |
|------------------------------------|------------|
| Component-Level certified          | yes        |
| Impedance                          | 100 Ohm    |
| Conductor cross section (AWG)      | AWG 24     |
| Conductor type                     | Stranded   |
| Crossed                            | no         |
| Locking lever                      | yes        |
| Anti-kink sleeve                   | Moulded-on |
| Colour (Spout)                     | white      |
| Cable LSOH                         | yes        |
| Side 1 Connector Type              | RJ-45      |
| Side 1 Connector Gender            | Male       |
| Side 2 Connector Type              | RJ-45      |
| Side 2 Connector Gender            | Male       |
| Connector Type RJ45                | Standard   |
| Weight                             | 114.7 g    |
| Height of packaging (single piece) | 30 mm      |
| Width of packaging (single piece)  | 180 mm     |
| Depth of packaging (single piece)  | 200 mm     |
| Package weight (single piece)      | 0.156 kg   |