ROLINE S/FTP Patch Cord Cat.6 Component Level, LSOH, white, 0.5 m

Product No. Manufacturer Manufacturer No. EAN (single piece)	21.15.2660 ROLINE 21.15.2660 7611990135998	roline Designed for Professionals
	$ \begin{array}{c} \hline \\ \hline $	
Cat.6 Class E		ONENT Tested

Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RI-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4pair stranded copper wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil. Halogen-free, flame retardant, low smoke.

100% Component Level testing

Technical specifications		
Manufacturer	ROLINE	
Product group	Twisted Pair Cable	
Product type	S/FTP Patchcord	
Colour	white	
Length	0.5 m	
Shield type	SFTP	
Transfer quality	Cat6 / Class E	

Component-Level certified	yes
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	black
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	28.4 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	160 mm
Depth of packaging (single piece)	120 mm
Package weight (single piece)	0.036 kg