## ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, grey, 2 m

**Product No.** 21.15.3305

Designed for Professio

Manufacturer

ROLINE


Manufacturer No.

21.15.3305

**EAN** (single piece)

7630049622197















Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

Technical specifications	
Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	FTP Patch Cord
Colour	grey
Length	2 m
Shield type	FTP

Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 32
Conductor type	Stranded
Crossed	no
Slim cable	yes
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	grey
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Weight	32.5 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	130 mm
Depth of packaging (single piece)	110 mm
Package weight (single piece)	0.037 kg