


# ROLINE U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, yellow, 5 m

|                    |               |                                                                                                                  |
|--------------------|---------------|------------------------------------------------------------------------------------------------------------------|
| Product No.        | 21.15.3327    | <br>Designed for Professionals |
| Manufacturer       | ROLINE        |                                                                                                                  |
| Manufacturer No.   | 21.15.3327    |                                                                                                                  |
| EAN (single piece) | 7630049622371 |                                                                                                                  |











**Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.**

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

| Technical specifications |                    |
|--------------------------|--------------------|
| Manufacturer             | ROLINE             |
| Product group            | Twisted Pair Cable |
| Product type             | FTP Patch Cord     |
| Colour                   | yellow             |
| Length                   | 5 m                |
| Shield type              | FTP                |

|                                    |                  |
|------------------------------------|------------------|
| Transfer quality                   | Cat6A / Class EA |
| Quantity of wires                  | 8                |
| Conductor cross section (AWG)      | AWG 32           |
| Conductor type                     | Stranded         |
| Crossed                            | no               |
| Slim cable                         | yes              |
| Locking lever                      | yes              |
| Anti-kink sleeve                   | Moulded-on       |
| Colour (Spout)                     | yellow           |
| Cable LSOH                         | yes              |
| Side 1 Connector Type              | RJ-45            |
| Side 1 Connector Gender            | Male             |
| Side 2 Connector Type              | RJ-45            |
| Side 2 Connector Gender            | Male             |
| Connector Type RJ45                | Standard         |
| Operating temperature min.         | -10 °C           |
| Operating temperature max.         | 60 °C            |
| Weight                             | 79.4 g           |
| Height of packaging (single piece) | 30 mm            |
| Width of packaging (single piece)  | 50 mm            |
| Depth of packaging (single piece)  | 50 mm            |
| Package weight (single piece)      | 0.08 kg          |