ROLINE Fibre Optic Jumper Cable, 50/125 μm, OM4, LC/LC, Armored, violet, 20 m

Product No. 21.15.8617

roline

Manufacturer ROLINE

Manufacturer No. 21.15.8617

EAN (single piece) 7630049621718





Halogen-free fiber optic patch cord with steel armouring in OM4 quality for highperformance fiber optic cabling in excellent ROLINE quality.

OM4 fiber is a 50 μ m laser-optimized fiber with extended bandwidth. It will be used to enhance the system performance for existing 1 and 10 Gbit/s applications as well as future 40 and 100 Gbit/s systems.

OM4 fiber will support Ethernet, Fibre Channel, and OIF applications, allowing extended reach upwards of 550 meters at 10 Gbit/s for ultra long building backbones and medium length campus backbones. With an laser bandwidth of 4700 MHz-km (more than double the IEEE requirement for 10 Gbit/s 300 meter support), the OM4 fiber is also especially well suited for shorter reach in data centers and high performance computing applications.

In use at low data rates such as 100 Mbit/s or 1 Gbit/s, OM4 is on par with the OM2 or OM3 fibers. The OM4 fiber shows their true strengths at data rates of 10 Gbit/s and 40 Gbit/s with ranges of 550 meters or 300 meters.

The quality of the connectors and fibres and an optimal assembly procedure lead to extremely good characteristics in respect of insertion loss and reflection

- These Fibre Optic Jumper cables are duplex cables with fiber type 50/125 μm
- Steel armored
- Compared to standard fiber optic patch cables, these cables are additionally protected by a flexible steel spiral helix
- Due to this high-quality cable construction, FO cables are tread-resistant and suitable for

applications with increased mechanical demands

- Only suitable for indoor use
- Colour: Violet

Technical specifications		
Manufacturer	ROLINE	
Product group	Fibre optic cable	
Product type	Fibre Optic Jumper Cables OM4	
Colour	violet	
Length	20 m	
Quantity of fibre	2	
Conductor composition	Compact conductor	
Cable type	Duplex Cable	
External cable	no	
Fibre section	Multi mode 50/125µm OM4	
Connection ports	LC / LC	
Side 1 Connector Type	LC	
Side 2 Connector Type	LC	
Colour (Cable)	violet	
Aramid strain relief	yes	
External cable diameter	3 mm	
Cable LSOH	yes	
Armouring	yes	
Max. insertion loss	0.3 dB	
Min. return loss	30 dB	
Weight	513.2 g	
Height of packaging (single piece)	30 mm	
Width of packaging (single piece)	180 mm	

Depth of packaging (single piece)	180 mm
Package weight (single piece)	0.5 kg