

ROLINE FO Jumper Cable 50/125µm OM3, LC/LC, Low-Loss-Connector, turquoise, 2 m

| | |
|--------------------|---------------|
| Product No. | 21.15.8822 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.8822 |
| EAN (single piece) | 7611990119981 |



LSOH

ROLINE F.O. Patchcable in OM3-Quality for a high performance connection.

- Security for the future! The OM3 fiber and connector quality with very low insertion loss ensure an excellent quality at very high bandwidths.
- Material and assembly in ROLINE quality
- The cable assembled with "low-loss" connectors achieve very good values for insertion loss and reflection. In comparison:
 - Typical attenuation of a standard LC connector: 0.5 dB
 - Typical attenuation of a low-loss LC connector: 0.15 dB
- Duplex cables with fiber type Multi-mode 50/125µm, OM3
- Color: turquoise

| Technical specifications | |
|--------------------------|-------------------------------|
| Manufacturer | ROLINE |
| Product group | Fibre optic cable |
| Product type | Fibre Optic Jumper Cables OM3 |
| Colour | turquoise |
| Length | 2 m |

| | |
|------------------------------------|-------------------------|
| Quantity of fibre | 2 |
| Conductor composition | Compact conductor |
| Cable type | Duplex Cable |
| External cable | no |
| Fibre section | Multi mode 50/125µm OM3 |
| Connection ports | LC / LC |
| Side 1 Connector Type | LC |
| Side 2 Connector Type | LC |
| Colour (Cable) | turquoise |
| Aramid strain relief | yes |
| External cable diameter | 2,8x6 mm |
| Mantle of external cable | LSOH |
| Cable LSOH | yes |
| Max. insertion loss | 0.15 dB |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 80 °C |
| Weight | 18.3 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 140 mm |
| Depth of packaging (single piece) | 210 mm |
| Package weight (single piece) | 0.029 kg |