

ROLINE FO Jumper Cable 50/125µm OM4, LSH/LC, UPC Polish, LSOH, violet, 3 m

| | |
|---------------------------|---------------|
| Product No. | 21.15.9473 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.9473 |
| EAN (single piece) | 7611990150588 |



High-quality fibre optic cables with the high protective, secured LSH connection on one side and LC plug on the other side - both connections are UPC polished.

- Duplex cable with 50/125µm OM4 fibre type
- Cable material: sheath halogen-free and flame-retardant, violet
- LC connector: plug with high mechanical load capacity, push-pull latched with anti-rotation device, ceramic ferrule
- LSH connector: precisely manufactured connector with low return loss, ceramic ferrule
- UPC Polish (Ultra Physical Contact)
- IL < 0.25dB, RL > 25dB
- IL (typical) < 0.12dB
- Cable OD (outer diameter): 3.0 x 6.0mm

Technical specifications

| | |
|-------------------|-------------------------------|
| Manufacturer | ROLINE |
| Product group | Fibre optic cable |
| Product type | Fibre Optic Jumper Cables OM4 |
| Colour | violet |
| Length | 3 m |
| Quantity of fibre | 2 |
| Cable type | Duplex Cable |

| | |
|---|-------------------------|
| External cable | no |
| Fibre section | Multi mode 50/125µm OM4 |
| Connection ports | LSH / LC |
| Side 1 Connector Type | LSH |
| Side 2 Connector Type | LC |
| Min. Bending radius, static | 30 mm |
| Min. Bending radius, dynamic | 60 mm |
| Aramid strain relief | yes |
| Cable LSOH | yes |
| Flame retardant according to IEC 60332- 1-2 | yes |
| Low smoke according to IEC 61034-2 | yes |
| Halogen free according to IEC 60754-2 | yes |
| Max. insertion loss | 0.2 dB |
| Min. return loss | 30 dB |
| RAL colour | RAL 4003 Heather violet |
| Weight | 53.8 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 200 mm |
| Depth of packaging (single piece) | 200 mm |
| Package weight (single piece) | 0.12 kg |