

ROLINE FO Jumper Cable Duplex, 9/125µm, OS2, LSH APC / LC UPC, LSOH, yellow, 0.5 m

Product No.	21.15.9510
Manufacturer	ROLINE
Manufacturer No.	21.15.9510
EAN (single piece)	7611990155194



LSOH

High-quality fibre optic cable with the high protective, secured APC polished LSH connection on one side and UPC polished LC plug on the other side.

- Duplex cable with fiber type 9/125µm OS2
- Cable material: sheath halogen-free and flame-retardant, yellow, solid core with aramid strain relief
- LC connector: connector with high mechanical load capacity, push-pull latched with anti-rotation lock, APC ground joint, ceramic ferrule
- LSH connectors: precision-manufactured connectors with low return loss, APC ground joint, ceramic ferrule, grey
- The LSH connector has a spring-loaded shutter, which fully protects the ferrule from dust and scratches
- LSH APC Polish (8°) / LC UPC Polish
- IL < 0.25dB, RL > 25dB
- IL (typical) < 0.12dB
- Cable OD (outer diameter): 3.0 x 6.0mm
- Remark: cable is available in 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m

Technical specifications

Manufacturer	ROLINE
Product group	Fibre optic cable
Product type	Fibre Optic Jumper Cables OS2
Colour	yellow
Length	0.5 m
Quantity of fibre	2
Cable type	Duplex Cable
External cable	no
Fibre section	Single mode 9/125µm OS2
Connection ports	LSH / LC UPC
Side 1 Connector Type	LSH
side 1 connector ferrules	APC Polish
Side 2 Connector Type	LC UPC
side 2 connector ferrules	UPC Polish
Min. Bending radius, static	30 mm
Min. Bending radius, dynamic	60 mm
Aramid strain relief	yes
Cable LSOH	yes
Flame retardant according to IEC 60332- 1-2	yes
Low smoke according to IEC 61034-2	yes
Halogen free according to IEC 60754-2	yes
Max. insertion loss	0.2 dB
Min. return loss	50 dB
Weight	17.8 g
Height of packaging (single piece)	10 mm

Width of packaging (single piece)	180 mm
Depth of packaging (single piece)	140 mm
Package weight (single piece)	0.028 kg