

# ROLINE FO Jumper Cable LSH Duplex, 9/125µm, OS2, LSH APC / LC UPC, LSOH, yellow, 3 m

<b>Product No.</b>	21.15.9513
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	21.15.9513
<b>EAN (single piece)</b>	7611990155637



**LSOH**

**High-quality fibre optic cable with the high protective, secured APC polished LSH connection on one side and UPC polished LC plug on the other side.**

- Duplex cable with fiber type 9/125µm OS2
- Cable material: sheath halogen-free and flame-retardant, yellow, solid core with aramid strain relief
- LC connector: connector with high mechanical load capacity, push-pull latched with anti-rotation lock, APC ground joint, ceramic ferrule
- LSH connectors: precision-manufactured connectors with low return loss, APC ground joint, ceramic ferrule, grey
- The LSH connector has a spring-loaded shutter, which fully protects the ferrule from dust and scratches
- LSH APC Polish (8°) / LC UPC Polish
  
- IL < 0.25dB, RL > 25dB
- IL (typical) < 0.12dB
- Cable OD (outer diameter): 3.0 x 6.0mm

## Technical specifications

Manufacturer	ROLINE
Product group	Fibre optic cable
Product type	Fibre Optic Jumper Cables OS2
Colour	yellow
Length	3 m
Quantity of fibre	2
Cable type	Duplex Cable
External cable	no
Fibre section	Single mode 9/125µm OS2
Connection ports	LSH / LC UPC
Side 1 Connector Type	LSH
side 1 connector ferrules	APC Polish
Side 2 Connector Type	LC UPC
side 2 connector ferrules	UPC Polish
Min. Bending radius, static	30 mm
Min. Bending radius, dynamic	60 mm
Aramid strain relief	yes
Cable LSOH	yes
Flame retardant according to IEC 60332- 1-2	yes
Low smoke according to IEC 61034-2	yes
Halogen free according to IEC 60754-2	yes
Max. insertion loss	0.2 dB
Min. return loss	50 dB
Weight	53.2 g
Height of packaging (single piece)	20 mm

Width of packaging (single piece)	200 mm
--------------------------------------	--------

Depth of packaging (single piece)	200 mm
--------------------------------------	--------

Package weight (single piece)	0.027 kg
----------------------------------	----------