


# ROLINE Cat.5e (Class D) Keystone Jack, RJ-45, UTP, light grey

|                    |               |  |
|--------------------|---------------|--|
| Product No.        | 26.11.0343    |  |
| Manufacturer       | ROLINE        |  |
| Manufacturer No.   | 26.11.0343    |  |
| EAN (single piece) | 7611990170548 |  |



## 19"-Patchpanel with Keystone Modules of ROLINE Quality!

- The system is composed of a 19" patch panel frame and the UTP Cat.5e RJ-45 keystone jack
  - Assembling takes place over LSA-plus
  - Colour code on the keystone jacks based on the standard EIA/TIA 568 A and 568 B
  - Colour: Light grey
  - For a structured unshielded Cat.5e cabling system we recommend to use the following components:  
ROLINE Cat.5e UTP Cable, Solid Wire, AWG24: 21.15.0512 (100 m), 21.15.0511 (300 m)  
ROLINE Flush Mount Wall Jack for Keystone, unloaded: 25.16.8579  
ROLINE Cat.5e Keystone, RJ-45, unshielded: 26.11.0343 (light grey), 26.11.0342 (black)  
ROLINE Cat.5e 19" Keystone Patch Panel, 24 Ports, unshielded: 26.11.0344 (black), 26.11.0345 (light grey)  
ROLINE Cat.5e UTP Patch Cord, grey, 5 m: 21.15.0505
- Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specification.

| Technical specifications |                          |
|--------------------------|--------------------------|
| Manufacturer             | ROLINE                   |
| Product group            | Connection technology TP |
| Product type             | RJ45 Keystone Jack       |



|                                    |                     |
|------------------------------------|---------------------|
| Colour                             | grey                |
| Shield type                        | Not screened        |
| Transfer quality                   | Cat5e / Class D     |
| Cabinet system                     | 19"-Technique       |
| Quantity of ports                  | 1                   |
| Assembly cable connection          | Krone LSAplus       |
| Assignment                         | EIA/TIA 568A & 568B |
| Modular assembly                   | yes                 |
| Connection direction               | Straight            |
| Height                             | 23 mm               |
| Width                              | 16.3 mm             |
| Depth                              | 31 mm               |
| Weight                             | 6.9 g               |
| Height of packaging (single piece) | 20 mm               |
| Width of packaging (single piece)  | 20 mm               |
| Depth of packaging (single piece)  | 50 mm               |
| Package weight (single piece)      | 0.009 kg            |