

ROLINE Cat.5e (Class D) 19" Patch Panel, 24 Ports, UTP, grey

| | |
|--------------------|---------------|
| Product No. | 26.11.0347 |
| Manufacturer | ROLINE |
| Manufacturer No. | 26.11.0347 |
| EAN (single piece) | 7611990159727 |



- The UTP patch panels are compliant with EIA/TIA 568 TSB40a
- LSA-plus technology
- 24 ports
- Colour: Light grey

For a structured unshielded cabling system we recommend to use the following components:

- ROLINE Cat.5e UTP Cable, Solid Wire, AWG24: 21.15.0512 (100 m), 21.15.0511 (300 m)
- ROLINE Cat.5e Flush/Surface Mount Wall Jack, unshielded: 25.16.8506 (white), 25.16.8501 (ivory)/25.16.8406 (white), 25.16.8401 (ivory)
- ROLINE Cat.5e 19" Patch Panel, 24 Ports, unshielded: 26.11.0349 (black), 26.11.0347 (light grey)
- ROLINE Cat.5e UTP Patch Cord, grey, 5 m: 21.15.0505

Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specifications.

| Technical specifications | |
|--------------------------|--------------------------|
| Manufacturer | ROLINE |
| Product group | Connection technology TP |
| Product type | Patchpanel Cat.5e |
| Colour | grey |

| | |
|------------------------------------|---------------------|
| Shield type | Not screened |
| Transfer quality | Cat5e / Class D |
| Cabinet system | 19"-Technique |
| Quantity of ports | 24 |
| Assembly cable connection | Krone LSAprus |
| Assignment | EIA/TIA 568A & 568B |
| Modular assembly | no |
| Shield contacts | No |
| Connection direction | Straight |
| Height units | 1 U |
| Height | 43.5 mm |
| Width | 482.6 mm |
| Depth | 48.3 mm |
| Weight | 485.2 g |
| Height of packaging (single piece) | 70 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 490 mm |
| Package weight (single piece) | 1 kg |