

ROLINE Keystone Holder, with Cat.6A Keystone, shielded, DIN-Rail, 45°

Product No.	26.11.0379
Manufacturer	ROLINE
Manufacturer No.	26.11.0379
EAN (single piece)	7630049635692



Keystone holder including shielded Cat.6A keystone, for installation on DIN rail

- Cable access 45° from the top or bottom, connection direction 45° downwards
- With shielded plate (grounding)
- keystones with printed colour coding in accordance with EIA/TIA 568
- Cables can be connected to the keystones without tools – simply place the cable wires in the guides, close the module and press it together – and the connection is complete
- Holder with integrated dust cover
- For cables with outer diameter: 5.0 - 8.0mm
- Suitable for 26AWG (0.40mm) - 22AWG (0.65mm) cables
- Dimensions Keystone Holder: 78.25 x 17.7 x 63.9mm
- Dimensions Keystone: 21.5 x 14.7 x 34.5 mm

Technical specifications	
Manufacturer	ROLINE
Product group	Connection technology TP
Product type	DIN rail adapter
Colour	grey
Scope of delivery	DIN-Rail Keystone Holder and Keystone, Installation Guide, Cable Tie
Shield type	Screened

Transfer quality	Cat6A / Class EA
Quantity of ports	1
Assignment	EIA/TIA 568A & 568B
Material (casing)	ABS + Zinc Alloy
Connection direction	45°-inclination
Dimensions (HxWxD)	Keystone Holder: 78.25 x 17.7 x 63.9mm, Keystone: 21.5 x 14.7 x 34.5 mm
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Storage temperature min.	-40 °C
Storage temperature max.	70 °C
Height	78.25 mm
Width	17.7 mm
Depth	63.9 mm
Weight	31 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	60 mm
Depth of packaging (single piece)	60 mm
Package weight (single piece)	0.05 kg