

ROLINE 19-inch wall-mounted housing Pro 12 U, 600x600 WxD two-part swivelling grey

Product No.	26.21.0012
Manufacturer	ROLINE
Manufacturer No.	26.21.0012
EAN (single piece)	7630049600133



ROLINE 19 inch wall-mounted housing Pro 12 U 600x600 WxD two-part swivelling grey

The wall-mounted enclosures in the ROLINE Pro series have been specially designed for flexible network cabling. The integrated hinge in the rear frame allows the enclosure to be folded to the side if required. Each enclosure has a sliding cable inlet with a foam rubber seal in the roof. The rear panel and base are fitted with punched cable inlets and plastic covers. The rear frame is fitted with brush strips at the top and bottom. The roof chassis is already provided with a suitable cut-out for installing a fan module. Inside there are galvanised 19" profile rails that can be read in both directions and are adjustable in depth. The rear frame also has 19" perforations. Each cabinet consists of a robust steel construction made of up to 1.5 mm thick sheet steel and is electrostatically powder-coated in the standard colours grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels and a lockable and removable front door improve accessibility. The door hinge can be changed.

Wall mounting is carried out in two simple steps: The frame of the enclosure is mounted on the wall in the desired opening direction and then connected to the enclosure. Optionally, the wall-mounted enclosures in the ROLINE Pro series can also be used free-standing with levelling feet or castors.

Technical specifications	
Manufacturer	ROLINE
Product group	19"- / 10" technology

Product type	19"-wall housing
Colour	grey
Scope of delivery	19-inch wall-mounted housing Pro 12 U, earthing cable set, installation set (screws, cage nuts, washers), 2x spanners
Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Model	With permanent frame
Height units	12 U
Minimum rack depth supported	320 mm
Maximum rack depth supported	450 mm
delivery condition	fully assembled
Material group	Steel
Material front door	Glass
Wall mountable	yes
Demountable	yes
Adjustable feets	no
Maximum weight capacity	80 kg
Protection class (IP Code)	IP20
Soundproof	no
Number of doors	1
With front door	yes
With backside door	no
With glazed door	yes
Front	Glass door
Rack rails	yes
Side panels included	yes
Removeable side panels	yes

Removable front door	yes
Removable back door	no
Ventilation	Passive
RAL colour	RAL 7035 Light grey
Height	640 mm
Width	600 mm
Depth	600 mm
Weight	34.9 kg
Height of packaging (single piece)	677 mm
Width of packaging (single piece)	660 mm
Depth of packaging (single piece)	635 mm
Package weight (single piece)	37.9 kg