

# ROLINE 19-inch server rack Pro 42 U, 600x1200 WxD grey

|                    |               |
|--------------------|---------------|
| Product No.        | 26.21.0155    |
| Manufacturer       | ROLINE        |
| Manufacturer No.   | 26.21.0155    |
| EAN (single piece) | 7630049601581 |



## ROLINE 19 inch server cabinet 42 U 600x1200 WxD grey

The server enclosures in the ROLINE Pro series have been specially developed for convenient and flexible network cabling. Inlets with brushes, a slide-on inlet with a foam rubber seal and an additional brush inlet in the base chassis are located on the sides of the roof and base (from 800 mm enclosure width), offering a wide range of possible applications. Perforated single-leaf front doors and double-leaf rear doors, each with a swivel handle and profile half cylinder, ensure improved air circulation. The roof has a perforated cover that allows easy installation of a fan module.

Two pairs of galvanised 19" profile rails are mounted inside the cabinet, which are equipped with height units that can be read in both directions and are adjustable in depth. They are also connected with depth braces. Each cabinet consists of a robust steel construction with a material thickness of up to 2.0 mm. The cabinets are electrostatically powder-coated and available in the standard colours grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels (horizontally divided from 42U) and doors improve accessibility. The door hinges can also be changed. The entire construction can be dismantled, meaning that the cabinets can be completely removed if required.

| Technical specifications |                    |
|--------------------------|--------------------|
| Manufacturer             | ROLINE             |
| Product group            | 19"-/10"-Cabinet   |
| Product type             | 19"-Server cabinet |

|                              |  |
|------------------------------|--|
| Colour                       | grey   |
| Scope of delivery            | 19-inch server enclosure 42 U, earthing cable set, installation kit for profile half cylinder, 2x spanners, installation set (screws, cage nuts, washers), assembly instructions |
| Type of profile rail         | L-shaped   |
| Modular spacing              | 482.6 mm (19 inch)   |
| Model                        | With permanent frame   |
| Height units                 | 42 U   |
| Minimum rack depth supported | 675 mm   |
| Maximum rack depth supported | 875 mm   |
| delivery condition           | fully assembled  |
| Material group               | Steel  |
| Material front door          | Steel  |
| Material rear door           | Steel  |
| Server cabinet               | yes  |
| Wall mountable               | no   |
| Adjustable feets             | yes  |
| Maximum weight capacity      | 1000 kg  |
| Protection class (IP Code)   | IP20   |
| Soundproof                   | no   |
| Number of doors              | 2  |
| With front door              | yes  |
| With backside door           | yes  |
| With glazed door             | yes  |
| Front                        | Steel door with perforation  |
| Backside                     | Steel door with perforation  |
| Rack rails                   | yes  |

|                                       |                     |
|---------------------------------------|---------------------|
| Side panels included                  | yes                 |
| Removeable side panels                | yes                 |
| Removable front door                  | yes                 |
| Removable back door                   | yes                 |
| Ventilation                           | Passive             |
| RAL colour                            | RAL 7035 Light grey |
| Height                                | 1970 mm             |
| Width                                 | 600 mm              |
| Depth                                 | 1200 mm             |
| Weight                                | 116.5 kg            |
| Height of packaging<br>(single piece) | 2150 mm             |
| Width of packaging<br>(single piece)  | 680 mm              |
| Depth of packaging<br>(single piece)  | 1280 mm             |
| Package weight (single<br>piece)      | 123 kg              |