


VALUE Dockingstation Type C, 2x HDMI 4K60, 1x DP 4K60, 1x Gigabit Ethernet, 5x USB A, 2x USB C, 1x Type C PD, 1x SD/microSD, 1x Audio

Product No.	12.99.1142
Manufacturer	VALUE
Manufacturer No.	12.99.1142
EAN (single piece)	7630049640764



Connect your Macbook, Ultrabook, Notebook/Laptop or PC with USB Type C interface to HDMI or DP displays/monitor or projectors (with a maximum resolution of up to 3840x2160@60Hz). Also, you can connect USB devices to the additional USB Type A Ports, while charging your device simultaneously over the Type C PD port!

- This docking station allows you to mirror or extend your display to your HDMI or DisplayPort monitor/display or projector
- 2x HDMI, 1x DisplayPort (max. resolution: 3840x2160 @60Hz)
- 1x Gigabit Ethernet (GbE - 1000Mbit/s)
- 1x C USB 3.2 Gen2 (10G) + 1x C USB 3.2 Gen1 (5G) + 2x A USB 3.2 Gen2 (10G) + 1x A USB 3.2 Gen1 (5G) + 2x A USB 2.0 (480Mbit/s)
- USB Type C PD (Power Delivery) up to 100 Watts
- 1x SD/TF Card Reader
- 1x 3.5mm Audio Out
- Full metal construction, ensuring effective heat dissipation
- Comes with stand and detachable magnetic base, supporting 360° horizontal rotation for enhanced adaptability in various application environments.

Remark: Support of "Alternate Mode (DP Alt Mode)" required

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has

been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

Technical specifications

Manufacturer	VALUE
Product group	Adapters, Terminators, Converters
Product type	Notebook-Docking-Station
Colour	grey
Length	0.1 m
Scope of delivery	Docking station, USB-C Host Cable, User Manual
Max. resolution	3840 x 2160 @60Hz (4K, UHD-1)
Side 1 connection (PC)	USB Type C
Side 2 connection (Peripherals)	2x HDMI, 1x DisplayPort, USB (5x A and 2x C), 1x USB-C PD (Power Delivery), 1x RJ-45 (GbE), 1x SD/TF Card Reader, 1x 3.5mm Audio Out
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	HDMI Type A DisplayPort USB Type C (USB-C) USB 3 Type A USB 2.0 Type A USB Type C PD (Power Delivery) RJ-45 SD-Card-Slot
Side 2 Connector Gender	Female
Area of application	External
Dimensions (HxWxD)	126 x 42 x 122 mm
Technical particularity	Power Delivery Function (100W)
Height	126 mm
Width	42 mm
Depth	122 mm

Weight	528 g
Height of packaging (single piece)	60 mm
Width of packaging (single piece)	160 mm
Depth of packaging (single piece)	200 mm
Package weight (single piece)	0.35 kg