## VALUE KVM Extender over Cat.6/6A, HDMI, max. 70m


**Product No.** 14.99.3042

Manufacturer VALUE

**Manufacturer No.** 14.99.3042

**EAN (single piece)** 7630049621268







## KVM extension over up to 70 m through the Cat.6/6A connection

- Supports HDMI with high resolution video up to 1920 x 1080 @ 60Hz (Full HD)
- Supports USB PC or KVM switch
- Ideal for professional video applications
- HDCP-compliant
- Supports EDID-Passthrough
- No drivers needed or software required
- · Stable, metal housing
- · Power supplied
- Receiver (RX) unit connectors: Monitor: 1x HDMI; 1x RJ-45 jack, 2x USB type A jack, 1x
- 3.5mm audio jack
- Transmitter (TX) unit connectors: Monitor: 2x HDMI; 1x RJ-45 jack, 1x USB type A jack

Technical specifications	
Manufacturer	VALUE
Product group	KVM (IP) extensions
Product type	KVM-Extender, HDMI
Colour	black
Scope of delivery	Transmitter unit, receiver unit, 2x power supply, manual
Max. distance	70 m

PC/Switch: monitor connection	HDMI
PC/Switch: mouse/keyboard connection	USB
Remote Console: Monitor connection	HDMI
Remote Console: Mouse/Keyboard connection	USB
Max. distance local- remote unit	70 m
Max. resolution (nominal)	1920 x 1080 (max.)
Material (casing)	metal
Dimensions (HxWxD)	19 x 85 x 75 mm
Power supply output	DC 5V, 2A
Operating temperature min.	0 °C
	0 °C 40 °C
min. Operating temperature	
min. Operating temperature max.	40 °C
min. Operating temperature max. Height	40 °C 19 mm
min. Operating temperature max. Height Width	40 °C  19 mm  85 mm
min. Operating temperature max. Height Width Depth	40 °C  19 mm  85 mm  75 mm
min.  Operating temperature max.  Height  Width  Depth  Weight  Height of packaging	40 °C  19 mm  85 mm  75 mm  247.3 g
min.  Operating temperature max.  Height  Width  Depth  Weight  Height of packaging (single piece)  Width of packaging	40 °C  19 mm  85 mm  75 mm  247.3 g  80 mm