VALUE KVM Extender over Cat. 6/6A, HDMI, 4K@60Hz, max. 120m

Product No. 14.99.3044


Manufacturer VALUE

Manufacturer No. 14.99.3044

EAN (single piece) 7630049633445









This is a 4K@60Hz HDMI KVM Extender Kit consisting of a transmitter and a receiver using ipcolor STREAM technology for high definition transmission with low latency. The 4K@60Hz HDMI signal can be extended up to 120m via Category 6 and higher network cables, supporting one-to-one connection, one-to-many connection via a gigabit switch and even switch cascading. It also supports HDMI Loop-Out and RS-232 Passthrough and can be used in meetings, home entertainment, educational presentations and other areas.

- Up to 3840 x 2160 @60Hz resolution, backwards compatible
- Transmission distance up to 120 meters, with Cat. 6 or above network cables
- Connections: one-to-one, one-to-many using a gigabit switch and cascading of gigabit switches
- ipcolor STREAM technology enables high-resolution and low-latency transmission
- Supports RS-232 passthrough
- Transmitter supports HDMI loop out
- Stable metal housing
- Transmitter (TX) ports: 1x HDMI in, 1x HMDI loop out, 1x RJ-45, 1x USB A, 1x USB Micro B (for firmware update), 1x RS-232, 1x 3.5mm in, 1x DC 5V
- Receiver (RX) ports: 1x HDMI out, 1x RJ-45, 2x USB A, 1x USB Micro B (for firmware update), 1x RS-232, 1x 3.5mm out, 1x DC 5V
- Dimensions Transmitter/Receiver (each): 21 x 103 x 106mm
- Weight: Transmitter 315g, Receiver 307g
- Contents: 1x Transmitter, 1x Receiver, 2x Power Adapter DC 5V 2A, 1x USB Cable A-A, 4x

| | Technical specifications |
|---|--|
| Manufacturer | VALUE |
| | |
| Product group | KVM (IP) extensions |
| Product type | KVM-Extender, HDMI |
| Colour | black |
| Scope of delivery | 1x Transmitter, 1x Receiver, 2x Power Adapter DC 5V 2A, 1x USB Cable A-A, 4x Mounting Ears, 2x Terminal block (RS-232), 1x User Manual |
| Audio | Stereo Audio |
| Max. distance | 120 m |
| PC/Switch: monitor connection | HDMI |
| PC/Switch: mouse/keyboard connection | USB |
| Remote Console: Monitor connection | HDMI |
| Remote Console: Mouse/Keyboard connection | USB |
| Max. distance PC- extension unit (local unit) | 5m |
| Max. distance local- remote unit | 120 m |
| Max. distance extension unit (remote unit)-console | 5m |
| Max. resolution (nominal) | 3840 x 2160@60Hz |
| Colour (Design profile) | black |
| Material (casing) | metal |
| | |

| Dimensions (HxWxD) | 21 x 103 x 106 mm |
|------------------------------------|-------------------|
| Power supply unit required | yes |
| Power supply output | DC 5V 2A |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -30 °C |
| Storage temperature max. | 70 °C |
| Height | 21 mm |
| Width | 103 mm |
| Depth | 106 mm |
| Weight | 622 g |
| Height of packaging (single piece) | 90 mm |
| Width of packaging (single piece) | 180 mm |
| Depth of packaging (single piece) | 250 mm |
| Package weight (single piece) | 1 kg |