

VALUE UPS, Line-Interactive, 1200VA, USB Port

Product No.	19.99.3430
Manufacturer	VALUE
Manufacturer No.	19.99.3430
EAN (single piece)	7611990930685



Quality Protection for Small Servers, Workstation & PC

- Line interactive design
- Boost and buck AVR (Auto voltage regulation)
- Fully digitized microprocessor controlled
- Energy saving function (UPS green mode)
- 50Hz frequency auto sensing and selection
- Cold start function (DC power on)
- Lightning and surge protection
- Short circuit and overload protection
- Advanced battery management (ABM technology)
- Tel/Modem internet surge suppression
- SmartUSB communication port
- Automatically charging when UPS off
- History record of power failure events
- Back up, on-line, battery status, power status display by software
- Schedule shutdown & reboot
- Windows 98/Me/NT/2000/XP/2003/7/8

Technical specifications	
Manufacturer	VALUE
Product group	UPS
Product type	UPS Line Interactive

Colour	black
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive
Power class	1000 ... 1900 VA
Output (VA/W)	1200 / 720
Efficiency	95 %
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	192 x 382 x 130 mm
Mounting form	Tower
Voltage (input)	230 V
Voltage (output)	230 V
Output voltage regulation	± 15 %
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C 14
Outputs	4
Connector type (output)	4x cold connector IEC320 C 13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	USB
USB 2.0 Interface	yes
Hot swap batteries	no

Bypass	no
Additional over current protector	Telephone/Fax
Activity	LED
Activity LED	1 LED
Activity Display	--
incl.Management Software	Windows
Internal cooling	Passive
Ambient temperature	0-40°C
Operating temperature min.	0 °C
Operating temperature max.	40 °C
Height	192 mm
Width	382 mm
Depth	130 mm
Weight	14 kg
Height of packaging (single piece)	320 mm
Width of packaging (single piece)	260 mm
Depth of packaging (single piece)	490 mm
Package weight (single piece)	14.64 kg

Back up time	
Capacity (VA / W)	minutes
200/120	40
400/240	18
600/360	9
800/480	5

1000/600	3
1200/720	2