## VALUE UTP Cable Cat.6 (Class E), halogen-free, grey, 3 m

**Product No.** 21.99.0203


Manufacturer VALUE

**Manufacturer No.** 21.99.0203

**EAN (single piece)** 7611990112951















Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded wire. Halogen-free, flame retardant, low smoke.

For a structured halogen-free cabling system we recommend to use the following components:

ROLINE Cat.6 UTP Cable, Solid Wire, LSOH, 300 m: 21.15.1789

VALUE Cat.6 Flush/Surface Mount Wall Jack, unshielded, white: 25.99.8494/25.99.8394

VALUE Cat. 6 19" Patch Panel, 24 Ports, unshielded: 26.99.0351 (black), 26.99.0352 (grey)

VALUE Cat.6 UTP Patch Cord, grey, LSOH: 21.99.0205

Technical specifications		
Manufacturer	VALUE	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	
Colour	grey	

Length	3 m
Shield type	UTP
Transfer quality	Cat6 / Class E
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 24
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	grey
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
RAL colour	RAL 7035 Light grey
Weight	81.7 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	140 mm
Depth of packaging (single piece)	140 mm
Package weight (single piece)	0.09 kg