## VALUE Outdoor S/FTP Patch Cord Cat.6A/Class EA, Solid, TPE, LSOH, black, 20 m

Product No. Manufacturer Manufacturer No. EAN (single piece)	21.99.0720 VALUE 21.99.0720 7630049627420	Value
	UTP = U/UTP FTP = F/UTP   UTP = U/UTP FTP = F/UTP   SFTP (Cat.6e) S/FTP (Cat.6)   SFTP (Cat.6e) S/FTP (PiMF)   Green: aluminium circl fuil ? Red: tinned copper braid	
Cat.6A Class EA	LSOH	

## Patch cord for outdoor use, e.g. for connecting an IP camera

Patch cords for networking connections between devices in combination with outdoor application (e.g. connection to outdoor surveillance cameras)

- Assembled double shielded (PiMF) twisted pair cable made of solid wire in category 6A with shielded RJ-45 connectors on both sides.
- Suitable for connecting external components (e.g. IP cameras), but also for PoE applications or as TP extension cable in multimedia applications
- UV resistant
- Durable thanks to molded bend protection
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Construction: 8 cores solid wire. Pair shielding: aluminum-clad polyester foil. Overall shielding: copper braiding
- High quality gold plated contacts

REMARK: NOT suitable for underground installation / application

Important: Not suitable for underground installation. RJ-45 connectors must be protected from the influence of the weather.

Technical specifications		
Manufacturer	VALUE	
Product group	Twisted Pair Cable	
Product type	S/FTP Patchcord	
Colour	black	
Length	20 m	
Shield type	PiMF	
Transfer quality	Cat6A / Class EA	
Quantity of wires	8	
Conductor cross section (AWG)	AWG 26	
Conductor type	Solid wire	
Crossed	no	
Locking lever	yes	
Anti-kink sleeve	Moulded-on	
Cable LSOH	yes	
Material (external cable mantle)	TPE	
Side 1 Connector Type	RJ-45	
Side 1 Connector Gender	Male	
Side 2 Connector Type	RJ-45	
Side 2 Connector Gender	Male	
Connector Type RJ45	Standard	
Operating temperature min.	-40 °C	
Operating temperature max.	60 °C	
Weight	704 g	
Height of packaging (single piece)	50 mm	

Width of packaging (single piece)	180 mm
Depth of packaging (single piece)	190 mm
Package weight (single piece)	0.6 kg