

# VALUE S/FTP Patch Cord Cat.6A (Class EA), green, 0.3 m

Product No.	21.99.1944
Manufacturer	VALUE
Manufacturer No.	21.99.1944
EAN (single piece)	7630049612396



**Cat.6A**  
Class EA

**S/FTP**

**LSOH**

The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz. Patch cable for networking connections between devices. Prepared shielded Twisted Pair cable (PIMF) with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Impedance: 100 Ohm. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 8 lines, pairs shielded with aluminium foil, complete braided shielding.

**For a structured shielded Cat.6a cabling system we recommend to use the following components:**

- VALUE Cat.6a S/FTP Cable, Solid Wire, 100 m: 21.99.0881.
- Flush Mount Wall Jack for Keystones: 25.16.8579.
- Surface Wall Mount Frame: 25.16.8484.
- VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366.
- 19" Keystone Patch Panel: 26.11.0359.
- VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0865.

Technical specifications	
Manufacturer	VALUE

Product group	Twisted Pair Cable
Product type	S/FTP Patchcord
Colour	green
Length	0.3 m
Shield type	SFTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 27
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	green
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	17.9 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	140 mm
Depth of packaging (single piece)	150 mm
Package weight (single piece)	0.025 kg