## ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, blue, 2 m


Product No. 21.44.3345

Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3345

**EAN (single piece)** 7630049624610















Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

ColourblueLength2 mScope of deliveryCable without plastic bag, only marked with a paper labelShield typeFTPTransfer qualityCat6A / Class EAQuantity of wires8Conductor cross section (AWG)AWG 32Conductor typeStrandedCrossednoSlim cableyesLocking leveryesAnti-kink sleeveMoulded-onColour (Spout)blueCable LSOHyesMaterial (external cable mantle)LSOH-TPESide 1 Connector TypeRJ-45Side 2 Connector GenderMaleSide 2 Connector Type RJ-45StandardOperating temperature min10 °COperating temperature min10 °C		
Scope of delivery  Shield type  FTP  Transfer quality  Cat6A / Class EA  Quantity of wires  8  Conductor cross section (AWG)  Conductor type  Stranded  Crossed  no  Slim cable  Locking lever  Colour (Spout)  blue  Cable LSOH  Material (external cable mantle)  Side 1 Connector Type  Side 2 Connector Type  RJ-45  Side 2 Connector Type RJ45  Side 2 Connector Type RJ45  Standard  Operating temperature min.  Operating temperature  min.  Operating temperature  Table  Cat6A / Class EA  AWG 32  AW	Colour	blue
Shield type FTP Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor cross section (AWG) 32 (AWG)  Conductor type Stranded  Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 3 Connector Type RJ-	Length	2 m
Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor cross section (AWG)  Conductor type Stranded  Crossed no  Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 3 Connector Type RJ-45	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG)  Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Conn	Shield type	FTP
Conductor cross section (AWG)  Conductor type Stranded  Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature  60 °C	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature foo °C	Quantity of wires	8
Crossed no Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes  Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature 60 °C		AWG 32
Slim cable Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type Side 1 Connector Gender  Side 2 Connector Gender  Side 2 Connector Gender  Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ-45  Side 3 Connector Gender  Side 4 Connector Gender  Side 5 Connector Connector Type All All All All All All All All All Al	Conductor type	Stranded
Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ-45  Operating temperature min.  Operating temperature 60 °C	Crossed	no
Anti-kink sleeve Moulded-on  Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Type RJ-45  Operating temperature of 0 °C	Slim cable	yes
Colour (Spout) blue  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature 60 °C	Locking lever	yes
Cable LSOH  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature 60 °C	Anti-kink sleeve	Moulded-on
Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature 60 °C	Colour (Spout)	blue
mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45 Standard  Operating temperature in the content of the	Cable LSOH	yes
Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature 60 °C		LSOH-TPE
Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature 60 °C	Side 1 Connector Type	RJ-45
Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature 60 °C		Male
Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature 60 °C	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min.  Operating temperature 60 °C		Male
min.  Operating temperature 60 °C	Connector Type RJ45	Standard
		-10 °C
		60 °C
Storage temperature -20 °C min.		-20 °C
Storage temperature 75 °C max.		75 °C

Weight	33.4 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	50 mm
Depth of packaging (single piece)	50 mm
Package weight (single piece)	0.04 kg