
ROLINE GREEN UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, grey, 3 m

Product No. Manufacturer Manufacturer No. EAN (single piece)

Class EA

21.44.3906 ROLINE GREEN 21.44.3906 7630049623798



Product

Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- $\ensuremath{\cdot}$ Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

| Technical specifications | | |
|--------------------------|--------------------|--|
| Manufacturer | ROLINE GREEN | |
| Product group | Twisted Pair Cable | |
| Product type | UTP Patch Cables | |

| Colour | grey |
|-------------------------------------|---|
| Length | 3 m |
| Scope of delivery | Cable without plastic bag, only marked with a paper label |
| Shield type | UTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 32 |
| Conductor type | Stranded |
| Crossed | no |
| Slim cable | yes |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | grey |
| Cable LSOH | yes |
| Material (external cable mantle) | LSOH-TPE |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -10 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 75 °C |
| | |

| Weight | 42.9 g |
|---------------------------------------|----------|
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 100 mm |
| Depth of packaging (single piece) | 100 mm |
| Package weight (single piece) | 0.048 kg |