ROLINE GREEN UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, red, 3 m

Product No. 21.44.3916


Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3916

EAN (single piece) 7630049623873

















Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	

Colour red Length 3 m Scope of delivery Cable without plastic bag, only marked with a paper label Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) AWG 32 Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) LSOH-TPE Side 1 Connector Type RJ-45 Side 1 Connector Gender Male Side 2 Connector Type RJ-45 Side 2 Connector Type RJ45 Standard Operating temperature min. -10 °C Starsage temperature min. -0 °C Starsage temperature max. 20 °C		
Scope of delivery Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable Locking lever Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type Side 2 Connector Type Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Standard Operating temperature min. Operating temperature min.	Colour	red
Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Length	3 m
Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-5 Standard Operating temperature nin. Operating temperature min.	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ65 Side 2 Connector Type RJ65 Side 2 Connector Type RJ65 Side 3 Connector Type RJ65 Side 4 Connector Type RJ65 Side 5 Connector Type RJ65 Side 6 Connector Type RJ65 Side 7 Connector Type RJ65 Side 8 Connector Type RJ65 Side 9	Shield type	UTP
Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Standard Operating temperature min. Operating temperature max.	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Operating temperature and contact the	Quantity of wires	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature max.		AWG 32
Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45 Standard Operating temperature min. Operating temperature foo °C	Conductor type	Stranded
Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Crossed	no
Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 9 Connector Type RJ-45 Standard Operating temperature min. Operating temperature max.	Slim cable	yes
Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Locking lever	yes
Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Anti-kink sleeve	Moulded-on
Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature foo °C max.	Colour (Spout)	red
Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature in the standard of	Cable LSOH	yes
Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature foo °C max.		LSOH-TPE
Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C max.	Side 1 Connector Type	RJ-45
Side 2 Connector Gender Connector Type RJ45 Operating temperature min. Operating temperature 60 °C max.		Male
Gender Connector Type RJ45 Standard Operating temperature in a control of the c	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min. Operating temperature 60 °C max.		Male
min. Operating temperature 60 °C max.	Connector Type RJ45	Standard
max.		-10 °C
Storage temperature 20 °C		60 °C
min.	Storage temperature min.	-20 °C
Storage temperature 75 °C max.		75 °C

Weight	43.4 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.048 kg