ROLINE GREEN UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, red, 5 m

Product No. 21.44.3917

Manufacturer ROLINE GREEN


Manufacturer No. 21.44.3917

7630049623880





EAN (single piece)













Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications			
Manufacturer	ROLINE GREEN		
Product group	Twisted Pair Cable		
Product type	UTP Patch Cables		

ColourredLength5 mScope of deliveryCable without plastic bag, only marked with a paper labelShield typeUTPTransfer qualityCat6A / Class EAQuantity of wires8Conductor cross section (AWG)AWG 32Conductor typeStrandedCrossednoSlim cableyesLocking leveryesAnti-kink sleeveMoulded-onColour (Spout)redCable LSOHyesMaterial (external cable mantle)LSOH-TPESide 1 Connector TypeRJ-45Side 1 Connector GenderMaleSide 2 Connector TypeRJ-45Side 2 Connector GenderMaleConnector Type RJ45StandardOperating temperature min10 °C		
Scope of delivery Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH Material (external cable mantle) Side 1 Connector Type Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ45 Standard Operating temperature -10 °C	r r	red
Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature -10 °C	h 5	5 m
Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45	of delivery C	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature -10 °C	l type U	UTP
Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature -10 °C	fer quality C	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45	ity of wires 8	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C		AWG 32
Slim cable Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type Gender Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45	actor type S	Stranded
Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 9 Connector Type RJ-45 Standard Operating temperature -10 °C	ed n	no
Anti-kink sleeve Moulded-on Colour (Spout) red Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature -10 °C	able y	yes
Colour (Spout) red Cable LSOH yes Material (external cable annule) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C	ng lever y	yes
Cable LSOH Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature -10 °C	ink sleeve M	Moulded-on
Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C	r (Spout) r	red
mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C	LSOH y	yes
Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature Male Standard Operating temperature Male Standard		LSOH-TPE
Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C	Connector Type R	RJ-45
Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature -10 °C		Male
Gender Connector Type RJ45 Standard Operating temperature -10 °C	? Connector Type R	RJ-45
Operating temperature -10 °C		Male
, , ,	ector Type RJ45 S	Standard
	iting temperature -:	-10 °C
Operating temperature 60 °C max.	iting temperature 6	60 °C
Storage temperature -20 °C min.	ge temperature -2	-20 °C
Storage temperature 75 °C max.	ge temperature 7	75 °C

Weight	68.1 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.068 kg