ROLINE GREEN UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, blue, 2 m

Product No. 21.44.3945


Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3945

7630049624108



EAN (single piece)













Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications			
Manufacturer	ROLINE GREEN		
Product group	Twisted Pair Cable		
Product type	UTP Patch Cables		

ColourblueLength2 mScope of deliveryCable without plastic bag, only marked with a paper labelShield typeUTPTransfer qualityCat6A / Class EAQuantity of wires8Conductor cross section (AWG)AWG 32Conductor typeStrandedCrossednoSlim cableyesLocking leveryesAnti-kink sleeveMoulded-onColour (Spout)blueCable LSOHyesMaterial (external cable mantle)LSOH-TPESide 1 Connector TypeRJ-45Side 2 Connector GenderMaleSide 2 Connector Type RJ-45MaleSide 2 Connector Type RJ45StandardOperating temperature min10 °C		
Scope of delivery Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable Locking lever Anti-kink sleeve Moulded-on Colour (Spout) Diue Cable LSOH Wes Material (external cable mantle) Side 1 Connector Type Side 2 Connector Type Side 2 Connector Gender Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Standard Operating temperature min. Operating temperature min. Operating temperature find 1 Cable Lone (Cable Cable Walled) Cable Lone (Cable Cable Walled) Cable Lone (Cable Cable Walled) Side 2 Connector Type Male Gender -10 °C Connector Type RJ-45 Standard	Colour	blue
Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side	Length	2 m
Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector	Shield type	UTP
Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ-45 Side 3 Connector T	Quantity of wires	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature 60 °C		AWG 32
Slim cable Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type Side 1 Connector Gender Side 2 Connector Side 2 Connector Gender Connector Type RJ-45 Standard Operating temperature min. Operating temperature 60 °C	Conductor type	Stranded
Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature 60 °C	Crossed	no
Anti-kink sleeve Moulded-on Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature of 0 °C	Slim cable	yes
Colour (Spout) blue Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Locking lever	yes
Cable LSOH Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Anti-kink sleeve	Moulded-on
Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Colour (Spout)	blue
mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature in the content of the	Cable LSOH	yes
Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C		LSOH-TPE
Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Side 1 Connector Type	RJ-45
Side 2 Connector Gender Connector Type RJ45 Operating temperature min. Operating temperature 60 °C		Male
Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min. Operating temperature 60 °C		Male
min. Operating temperature 60 °C	Connector Type RJ45	Standard
		-10 °C
ιτιαλ.	Operating temperature max.	60 °C
Storage temperature -20 °C min.		-20 °C
Storage temperature 75 °C max.		75 °C

Weight	30.5 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.03 kg