## ROLINE RM S/FTP (PiMF) Patch Cord Cat.6A, grey, 7 m

**Product No.** 21.45.3206

ROLINE RECYCLED MATERIAL


Manufacturer No. 21.45.3206

**EAN (single piece)** 7630049631236



Manufacturer





roline :





The patch cables in the ROLINE RECYCLED MATERIAL product line with shielded RJ-45 connectors are ideal for 10 Gigabit Ethernet networks. Gold-plated contacts and moulded bend protection ensure durability and reliable performance.

- Patch cable for networking connections between devices
- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire
- Complete braid shielding. Pairs shielded with aluminium clad polyester foil

## ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

| Technical specifications |                          |  |
|--------------------------|--------------------------|--|
| Manufacturer             | ROLINE RECYCLED MATERIAL |  |
| Product group            | Twisted Pair Cable       |  |
| Product type             | S/FTP Patchcord          |  |

| Colour                             | grey             |
|------------------------------------|------------------|
| Length                             | 7 m              |
| Shield type                        | SFTP             |
| Transfer quality                   | Cat6A / Class EA |
| Quantity of wires                  | 8                |
| Conductor cross section (AWG)      | AWG 26           |
| Conductor type                     | Stranded         |
| Crossed                            | no               |
| Locking lever                      | yes              |
| Anti-kink sleeve                   | Moulded-on       |
| Side 1 Connector Type              | RJ-45            |
| Side 1 Connector<br>Gender         | Male             |
| Side 2 Connector Type              | RJ-45            |
| Side 2 Connector<br>Gender         | Male             |
| Connector Type RJ45                | Standard         |
| Operating temperature min.         | -20 °C           |
| Operating temperature max.         | 75 °C            |
| Storage temperature min.           | -20 °C           |
| Storage temperature max.           | 80 °C            |
| Weight                             | 213.6 g          |
| Height of packaging (single piece) | 30 mm            |
| Width of packaging (single piece)  | 120 mm           |
|                                    |                  |

| Depth of packaging (single piece) | 120 mm |
|-----------------------------------|--------|
| Package weight (single piece)     | 0.2 kg |