


ROLINE RM S/FTP (PiMF) Patch Cord Cat.6A, red, 3 m

Product No. 21.45.3213
Manufacturer ROLINE RECYCLED MATERIAL
Manufacturer No. 21.45.3213
EAN (single piece) 7630049631328



The patch cables in the **ROLINE RECYCLED MATERIAL** product line with shielded **RJ-45** connectors are ideal for **10 Gigabit Ethernet** networks. **Gold-plated contacts** and **moulded bend protection** ensure **durability** and **reliable performance**.

- Patch cable for networking connections between devices
- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire
- Complete braid shielding. Pairs shielded with aluminium clad polyester foil

ROLINE RECYCLED MATERIAL products consist of more than **50% recycled materials**. The packaging is even made from **100% recycled material**.

Technical specifications	
Manufacturer	ROLINE RECYCLED MATERIAL
Product group	Twisted Pair Cable
Product type	S/FTP Patchcord

Colour	red
Length	3 m
Shield type	SFTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-20 °C
Operating temperature max.	75 °C
Storage temperature min.	-20 °C
Storage temperature max.	80 °C
Weight	93.2 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm

Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.1 kg