ROLINE EV Charging Cable Assembly Type2, 1-Phase, 250VAC (1P+N+E), 32 A, 7.4 kW, 3 m

Product No. 19.08.0003

ROLINE

Manufacturer ROLIN

Manufacturer No. 19.08.0003

EAN (single piece) 7630049628069







Type2 charging cable for electric and hybrid cars with 7.4 kW, 1-phase, 250 V AC

- Enables easy / fast charging at public charging stations and private wall boxes (wallbox)
- Suitable for charging electric and hybrid vehicles
- Mode 3 / Type 2 car charging cable
- Connections: Type 2 on both sides
- For all electric cars with type 2 connection
- Ergonomically shaped plug and coupler
- Moisture protection (IP65 connected state, IP54 unconnected cable with protective caps attached)
- 32A / 1- phase (250 VAC)
- Max. Charging power: 7,4 kW

Technical specifications		
Manufacturer	ROLINE	
Product group	Power Cables	
Product type	Electric car charging cable	
Colour	black	
Length	3 m	
Scope of delivery	E-car charging cable, carrying bag	

Charging power	7.4 kW
Current	32 A
Number of phases	1-phase
Supported charging technology	Mode-3
Side 1 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 1 Connector Gender	Male
Side 2 Connector Type	IEC 62196-2 Type 2 (VDE-AR-E 2623-2-2)
Side 2 Connector Gender	Female
Cable LSOH	flame retardant
Protection class (IP Code)	IP65 IP54
Mains connection	IEC 62196-2 Type 2 plug, 1Ph.
Operating temperature min.	-30 °C
111111.	
Operating temperature max.	50 °C
Operating temperature	50 °C 80 mm
Operating temperature max.	
Operating temperature max. Height	80 mm
Operating temperature max. Height Width	80 mm 360 mm
Operating temperature max. Height Width Depth	80 mm 360 mm 360 mm
Operating temperature max. Height Width Depth Weight Height of packaging	80 mm 360 mm 360 mm 2.1 kg
Operating temperature max. Height Width Depth Weight Height of packaging (single piece) Width of packaging	80 mm 360 mm 2.1 kg 80 mm