

ROLINE DesignSecure 625

Product No.	19.40.1206
Manufacturer	ROLINE
Manufacturer No.	19.40.1206
EAN (single piece)	7611990171026



- Compact designed UPS in futuristic design
- For Workstations and PCs
- LineInteractive UPS
- AVR (Automatic Voltage Regulation)
- Digital status display
- Integrated overvoltage protection
- Telephone/Modem connections
- USB Port for advanced Power Management Software (incl. in content of delivery)
- EMI/RFI Noise Filter
- Dimensions (HxLxW) 168 x 105 x 334 mm
- Weight: 6.3 kg
- Backup Time: up to 4 Minutes

Technical specifications

Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive
Colour	black /silver
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive

Power class	600 ... 900 VA
Output (VA/W)	625 / 375
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	168 x 105 x 334 mm
Mounting form	Turm
Voltage (input)	230 V
Voltage (output)	230 V
Output voltage regulation	yes
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C14
Outputs	5
Connector type (output)	2x 3 cold connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	USB
USB 2.0 Interface	Yes
Hot swap batteries	No
Bypass	No
Additional over current protector	Telephone/Fax
Activity	Display
Activity LED	--
Activity Display	yes

incl.Management Software	Windows
Internal cooling	Passive
Ambient temperature	0-40 °C
Operating temperature min.	0 °C
Operating temperature max.	40 °C
Height	168 mm
Width	105 mm
Depth	334 mm
Weight	6.4 kg
Height of packaging (single piece)	270 mm
Width of packaging (single piece)	210 mm
Depth of packaging (single piece)	420 mm
Package weight (single piece)	6.96 kg

Backup Time

Capacity (VA / W)	minutes
100	50
200	19
300	8
425	5
525	4
625	3