

ROLINE DesignSecure 1200

Product No.	19.40.1212
Manufacturer	ROLINE
Manufacturer No.	19.40.1212
EAN (single piece)	7611990976768

roline
Designed for Professionals



- Compact designed UPS in futuristic design
- For Workstations and PCs
- LineInteractive UPS
- AVR (Automatic Voltage Regulation)
- Digital status display
- Integrated overvoltage protection
- Telephone/Modem connections
- USB Port for advanced Power Management Software (incl. in content of delivery)
- EMI/RFI Noise Filter
- Dimensions (HxLxW) 168 x 105 x 334 mm
- Weight: 6.3 kg
- Backup Time: up to 4 Minutes

Technical specifications

Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive
Colour	black /silver
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive

Power class	1000 ... 1900 VA
Output (VA/W)	1200 / 720
Backup time	3 min
Backup time full/half-load	3 / 6 min
Dimensions (HxWxD)	168 x 105 x 334 mm
Mounting form	Turm
Voltage (input)	230 V
Voltage (output)	230 V
Output voltage regulation	yes
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C14
Outputs	4
Connector type (output)	4 cold connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	USB
USB 2.0 Interface	Yes
Hot swap batteries	No
Bypass	No
Additional over current protector	Telephone/Fax
Activity	Display
Activity LED	--
Activity Display	yes

incl.Management Software	Windows
--------------------------	---------

Internal cooling	Passive
------------------	---------

Ambient temperature	0-40 °C
---------------------	---------

Operating temperature min.	0 °C
----------------------------	------

Operating temperature max.	40 °C
----------------------------	-------

Height	192 mm
--------	--------

Width	130 mm
-------	--------

Depth	382 mm
-------	--------

Weight	14 kg
--------	-------

Height of packaging (single piece)	310 mm
------------------------------------	--------

Width of packaging (single piece)	260 mm
-----------------------------------	--------

Depth of packaging (single piece)	490 mm
-----------------------------------	--------

Package weight (single piece)	14.784 kg
-------------------------------	-----------

Backup Time

Capacity (VA / W)	minutes
-------------------	---------

200/120	40
---------	----

400/240	18
---------	----

600/360	9
---------	---

800/480	5
---------	---

1000/600	3,5
----------	-----

1200/720	2,5
----------	-----