

# ROLINE Outdoor S/FTP Patch Cord Cat.6A / Class EA, Stranded, TPE, LSOH, black, 0.5 m

<b>Product No.</b>	21.15.0750
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	21.15.0750
<b>EAN (single piece)</b>	7630049627451

**roline**  
Designed for Professionals



**Cat.6A**  
Class EA

**S/FTP**

**LSOH**

**Assembled double shielded (PiMF) twisted pair cable category 6A with shielded RJ-45 connectors on both sides. For outdoor use (cable routing), e.g. for connecting an IP camera.**

Patch cord for networking connections between devices in combination with outdoor application (e.g. connection to outdoor surveillance cameras)

- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Suitable for PoE applications and multimedia applications where the extension is working over TP
- High quality plugs with gold plated contacts
- UV - resistant (Ultraviolet resistance - ability of the material to withstand the degradation that can be caused by exposure to ultraviolet light)
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire, complete braid shielding, pairs shielded with aluminium foil

REMARK: NOT suitable for underground installation / application

**Technical specifications**

Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	S/FTP Patchcord
Colour	black
Length	0.5 m
Shield type	PiMF
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Conductor type	Wire
Crossed	no
Bend radius	Min. 25mm
External cable diameter	6.0 +/-0.2mm
Cable LSOH	yes
Material (external cable mantle)	TPE
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-40 °C
Operating temperature max.	75 °C
Weight	23.1 g
Height of packaging (single piece)	10 mm

---

Width of packaging (single piece)	150 mm
--------------------------------------	--------

Depth of packaging (single piece)	200 mm
--------------------------------------	--------

Package weight (single piece)	0.3 kg
----------------------------------	--------