

# ROLINE Cat.5e (Class D) 19" Patch Panel, 24 Ports, STP, grey

<b>Product No.</b>	26.11.0329
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	26.11.0329
<b>EAN (single piece)</b>	7611990147786



- The panels comply with the EIA / TIA 568 Cat. 5e TSB40A standard
- The cable connection on the back is implemented via LSA-plus connection technology with colour coding on the top in accordance with EIA/TIA 568
- Sheet steel housing and cover
- 24 ports
- Colour: Light grey

For a structured cabling system we recommend to use the following components:

ROLINE Cat.5e S/FTP Cable, Solid Wire, AWG24: 21.15.0019 (100 m), 21.15.0020 (300 m)

ROLINE Cat.5e Flush/Surface Mount Wall Jack, shielded: 25.16.8487 (white), 25.16.8486 (ivory)/25.16.8387 (white), 25.16.8386 (ivory)

ROLINE Cat.5e 19" Patch Panel, 24 Ports, shielded: 26.11.0329 (light grey), 26.11.0328 (black)

ROLINE Cat.5e S/FTP Patch Cord, grey, 5 m: 21.15.0305

Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specifications.

## Technical specifications

Manufacturer	ROLINE
Product group	Connection technology TP
Product type	Patchpanel Cat.5e

Colour	grey
Shield type	Screened
Transfer quality	Cat5e / Class D
Cabinet system	19"-Technique
Quantity of ports	24
Assembly cable connection	Krone LSAplus
Assignment	EIA/TIA 568A & 568B
Modular assembly	No
Material (casing)	Metal
Shield contacts	Yes
separate strain relief	Yes
Connection direction	Straight
Height units	1 U
Height	44 mm
Width	482.6 mm
Depth	136 mm
Weight	1505.7 g
Height of packaging (single piece)	80 mm
Width of packaging (single piece)	250 mm
Depth of packaging (single piece)	570 mm
Package weight (single piece)	2.2 kg